

Electrical Data

| | | |
|------------------------|------------------------|-----------------|
| Frequency: | 806-960 MHz | 1710-2700 MHz |
| Gain: | 10 dBi(±0.5dBi) | 11 dBi(±0.5dBi) |
| VSWR: | <1.7:1 | <1.5:1 |
| Polarization: | Horizontal Or Vertical | |
| Horizontal Beamwidth : | 58°(±8°) | |
| Vertical Beamwidth: | 47°(±6°) | |
| Nominal Impedance: | 50 Ohms | |
| F/B Ratio: | >25 dB | |
| Max Input Power: | 350 W | |
| Lightning Protection: | DC Ground | |

Mechanical Data

| | |
|------------------------|-------------------|
| Connector : | N Female |
| Dimension: | 400*265*65mm |
| (length*width*height) | /15.7*10.4*2.6 in |
| Weight: | 1kg/2.2lb |
| Cable Length: | 380mm/15.0in |
| Reflector Material: | Aluminum Alloy |
| Radome Material: | Weatherproof ABS |
| Mounting Method: | Mast |
| Mast Size: | Ø40-Ø50mm |
| Rated Wind Velocity: | 210km/h |
| Operating temperature: | -40~+65℃ |

Shipment Data

| | |
|-----------------------|------------------|
| Packing Qty: | 10pcs/Carton |
| Carton Size: | 580*450*450mm |
| (length*width*height) | 22.8*17.7*17.7in |
| Packing Weight: | 11kg/24.2lb |

